



4700 W. 160th St.
 Cleveland, OH 44135
 PH:800-321-9532
 FX:800-321-9535
 www.oatey.com
 TECHNICAL SPECIFICATION

**MULTI-SIZE (MS)
 END-CAP™ TEST CAPS**



TECHNICAL SPECIFICATION: Oatey Multi-Size (MS) End-Cap Test Caps are a solvent weld test cap designed for testing up to 15 PSI or 40' head pressure. Multi-Size design allows for use on 1.5" and 2" or 3" and 4" piping. End-Cap Test Caps deep design provides extra sealing strength. End-Cap Test Caps can be used on Schedule 40 ABS or PVC DWV piping.



PHYSICAL/CHEMICAL PROPERTIES

Material White PVC and Black ABS
 Color White or Black

DIRECTIONS FOR USE

Solvent weld MS End-Cap test cap to end of pipe and conduct hydrostatic pressure test up to 17 PSI or 40' head pressure.

PRECAUTIONS

Do not stand in the danger zone while test is in progress.
 Never test piping system using compressed air.

COMMON APPLICATIONS

MS End-Cap Test Caps are a solvent weld test cap designed for testing up to 15 PSI or 40' head pressure. Multi-Size design allows for use on 1.5" and 2" or 3" and 4" piping.

Consult Oatey Technical Department for applications not specifically referenced above.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
33478	1-1/2" - 2" MS End-Cap - PVC (50 in polybag)	500	18.5 lbs.
33479	1-1/2" - 2" MS End-Cap - ABS (50 in polybag)	500	18.5 lbs.
39115	1-1/2" - 2" MS End-Cap with Barcode - PVC	25	1 lb.
33480	3" - 4" MS End-Cap - PVC (25 in polybag)	200	18.5 lbs.
33481	3" - 4" MS End-Cap - ABS (25 in polybag)	200	18.5 lbs.
39116	3" - 4" MS End-Cap with Barcode - PVC	25	2 lb.