

SLIM LINE®



W38-PRA

W385-PR

- Point-of-Use filter housings
- 3/8-inch NPT inlet/outlet
- 5- and 10-inch lengths
- Pressure relief button
- WMB38 Mounting Bracket included

MODEL NUMBER	PART NUMBER	SUMP COLOR	CAP COLOR	INLET/OUTLET	OVERALL DIMENSIONS	OPERATING PRESSURE	OPERATING TEMPERATURE	OPTIONAL ACCESSORIES†
W385-PR	152007	Gray	Black	3/8" NPT	4-1/2" x 7"	30 - 125 psi	40 - 100° F	WW38
W38-PRA	152005	Gray	Black	3/8" NPT	4-1/2" x 7"	30 - 125 psi	40 - 100° F	WW38

STANDARD



W34-PR

WC34-PR

- Whole-house filter housings
- 3/4-inch NPT inlet/outlet
- Pressure relief button
- Clear or opaque sump
- Accepts a wide variety of 2-1/2 to 3-inch diameter cartridges

MODEL NUMBER	PART NUMBER	SUMP COLOR	CAP COLOR	INLET/OUTLET	OVERALL DIMENSIONS	OPERATING PRESSURE	OPERATING TEMPERATURE	OPTIONAL ACCESSORIES†
W34-PR*	152047	Gray	Black	3/4" NPT	5-1/8" x 12-1/4"	30 - 125 psi	40 - 100° F	WMB34, WW34
WC34-PR	152018	Clear	Black	3/4" NPT	5-1/8" x 12-1/4"	30 - 125 psi	40 - 100° F	WMB34, WW34

*Not Performance Tested or Certified by NSF.

VALVE-IN-HEAD



WVC34

- Whole-house filter housing
- Valve-in-Head (VIH) closes both the inlet and outlet port simultaneously, making cartridge change-outs quick and easy
- 3/4-inch NPT inlet/outlet
- Pressure relief button
- Accepts a wide variety of 2-1/2 to 3-inch diameter cartridges



Tested and Certified by NSF International.

MODEL NUMBER	PART NUMBER	SUMP COLOR	CAP COLOR	INLET/OUTLET	OVERALL DIMENSIONS	OPERATING PRESSURE	OPERATING TEMPERATURE	OPTIONAL ACCESSORIES†
WVC34	152003	Clear	Black	3/4" NPT	5-1/8" x 12-1/4"	30 - 125 psi	40 - 100° F	WMB34, WW34

†See page 14 for part number and description. Note: See chart on page 16 for flow rates with specific cartridges.