

WIC-600 QUICK CHANGE

- Point-of-Use filter system
- Icemaker/water dispenser water system
- Change filter with easy 1/4 turn, no spilling of water
- Includes all installation hardware
- Works with copper, plastic or flexible tubing
- Reduces lead, Cysts*, Lindane, Atrazine, chlorine taste & odor and sediment



Tested and Certified by NSF International.

MODEL NUMBER	PART NUMBER	REDUCES	INLET/OUTLET	OVERALL DIMENSIONS	RATING	OPERATING PRESSURE	OPERATING TEMPERATURE
WIC-600	158582	Lead, Cysts*, Lindane, Atrazine, Chlorine Taste & Odor, Sediment	1/4"	3" x 3" x 13-1/2"	0.5 micron	30 - 125 psi	40 - 100° F
Replacement Cartridge							
600R	155785-51	Lead, Cysts*, Lindane, Atrazine, Chlorine Taste & Odor, Sediment	—	2-1/2" x 2-1/2" x 12-1/2"	0.5 micron	30 - 125 psi	40 - 100° F

*NSF/ANSI Standard 53 certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means.



QUICK CONNECT IN-LINE

- Point-of-Use filters
- Refrigerator icemakers and water dispensers, coffee makers and other in-line applications
- Granular-activated carbon reduces bad taste and odor and chlorine taste & odor from water
- WICSA includes phosphate crystals to prevent lime/scale build-up. Not Performance Tested or Certified by NSF.
- Quick-connect fittings attach easily to 1/4" -copper or plastic cold water lines
- Polypropylene pre and postfilters



Tested and Certified by NSF International. for material requirements only!

MODEL NUMBER	PART NUMBER	MEDIUM	FLOW RATE (GPM)	OPERATING PRESSURE	TEMPERATURE RANGE	DIAMETER	LENGTH
WIC-6A	155702-51	Granular Activated Coconut Carbon	0.5	20 - 125 psi	40 - 100° F	2"	6"
WICA	155070-51	Granular Activated Coconut Carbon	8.5	20 - 125 psi	40 - 100° F	2"	10"
WICSA	155083-51	Granular Activated Coconut Carbon & Phosphate Crystals	0.5	20 - 125 psi	40 - 100° F	2"	10"
WIC	255521-51	Granular Activated Coconut Carbon	1.0	20 - 125 psi	40 - 100° F	2"	10"

