



# **SmartMate**

## SMARTMATE ICF2S18H1LDK

Offering maximum versatility, the Philips Advance family of SmartMate ballasts for 4-pin compact fluorescent lamps drive a broad range of quad and triple-tube, circline, 2D, and long twin-tube lamps. SmartMate ballasts' energy efficient design, compact and lightweight housing, and user-friendly features make these ballasts an ideal choice for fixture manufacturers, retrofitters, and MRO replacement.

#### **Product data**

General Information					
Lamp Type	CFQ18W/G24Q				
Number Of Lamps	1/2 piece/unit				
Ballast Type	Electronic Fluorescent				
Base Model	ICF2S18H1LD				
Suitable For Outdoor Use	Yes				
Automatic Restart	Yes				
Operating and Electrical					
Input Voltage	120 to 277 V				
Input Frequency	50 to 60 Hz				
Total Harmonic Distortion USA	10 %				
Ignition Method	Programmed Start				
Crestfactor (Nom)	1.5				
Ignition Time (Nom)	1.5 s				
Ballast Factor (Nom)	0.95				
Power Factor (Nom)	0.98				
Input Current (Max)	0.30 A				
Input Current (Min)	0.13 A				
Input Power (Nom)	35-35 W				


Poted Long Device	18 W		
Rated Lamp Power	18 W		
Wiring			
Color Input Terminals	Black and White		
Color Output Terminals	RED, YEL & BLU		
Wire Striplength	0.375 mm		
Lamp Connection	Series		
Wire Length By Color	No wires		
Wire Gauge (Nom)	18AWG mm		
Wire Type	Solid		
Remote Wiring Configuration Allowed	Yes		
Tandem Wiring Configuration Allowed	Yes		
Through Wiring Configuration Allowed	Yes		
Max Ballast-Lamp Distance Remote Wiring	1-L = 15' / 2-L = 6'		
Max Ballast-Lamp Distance Tandem Wiring	2-L: Red = 6'		
Max Ballast-Lamp Distance Through Wiring	2-L: Red = 6'		
Connector Type	Poke-In		
Temperature			
T-Case Maximum (Nom)	75 °C		

### **SmartMate**


Mechanical and Housing				
Housing Material	Metal/Plastic			
Housing	H1			
Housing Dimensions	4.98" x 2.4" x 0.98"			
Approval and Application				
EMC Immunity Standard	FCC Non-Consumer			
Approval Marks	CSA certificate UL certificate CEC Listing RoHS			
	Compliant			
Hum And Noise Level	A			
UL Recognized	No			

Product Data					
Order product name	SMARTMATE ICF2S18H1LDK				
EAN/UPC - Product	781087117767				
Order code	913700500821				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	12				
Material Nr. (12NC)	913700500821				
Net Weight (Piece)	250.000 g				

#### **Dimensional drawing**



Product	A1	A2	A3	B1	C1
SMARTMATE ICF2S18H1LDK	4.60 in	4.20 in	2.00 in	3.00 in	1.29 in





© 2015 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2015, December 23 - data subject to change