



## RWA-Flexible Conduit REDUCED WALL ALUMINUM

Part Number	Internal Diameter		External Diameter		Bending Radius	Weight lbs per 100 ft.
	Min (inch)	Max (inch)	Min (inch)	Max (inch)		
RWA-3/8	0.375	0.393	0.560	0.610	2.00	7
RWA-1/2	0.625	0.645	0.860	0.920	3.00	10
RWA-3/4	0.812	0.835	1.045	1.105	4.00	11
RWA-1	1.000	1.040	1.300	1.380	5.00	20
RWA-1-1/4	1.250	1.300	1.550	1.630	6.25	22
RWA-1-1/2	1.500	1.575	1.850	1.950	7.50	44
RWA-2	2.000	2.080	2.350	2.450	10.00	44
RWA-2-1/2	2.500	-	2.860	3.060	12.50	60
RWA-3	3.000	-	3.360	3.560	15.00	74
RWA-3-1/2	3.500	-	3.860	4.060	17.50	106
RWA-4	4.000	-	4.360	4.560	20.00	128

All values are nominal and subject to correction.

- Application:** Allows electrical contractors to run hundreds of feet of conduit without installing connectors between sections of conduit or the need for frequent braces to support the weight.
- Construction:** Light weight, primary, tempered aluminum alloy provides maximum strength and flexibility. Superior resistance to corrosion with a smooth interior for easy pull through. Built in flexibility provides easy installation.
- Standards:** Complies with UL-1 File Number E25633  
 NEC Article 350 and WW-C-566C  
 UL 1479 File Number 14879  
 ANSI Standards E119 and E814  
 1/3 weight of steel  
 3/8" RWA is CSA Certified File Number 14901

**1-800-945-5542**