



LOW-VOC SOLVENT CEMENTS

Apply all solvent cements in conjunction with RectorSeal primer

Gene™ 404L Clear - regular body PVC solvent cement

Code	Description	Qty.
55901	¼ pt.	24
55902	½ pt.	24
55904	1 pt.	12
55906	1 qt.	12
55908	1 gal.	4

Fast Setting for use on PVC pipe and fittings Schedule 40 through 2" pressure piping and 4" non-pressure (DWV). Not recommended for use on Schedule 80 pipe.*

See recommended use chart on page 8



Hot™ 203L Blue - medium body PVC solvent cement

Code	Description	Qty.
55988	¼ pt.	24
55989	½ pt.	24
55990	1 pt.	12
55993	1 qt.	12
55994	1 gal.	4

Very fast setting for use on rigid PVC pipe and fittings through 6" for Schedule 40 and 1 ¼" for Schedule 80. May also be used on flexible PVC hose with rigid fittings or hose to hose insertion-type connections. Uses include plumbing for irrigation, pools, spas and ENT.*

See recommended use chart on page 8



Pete™ 602L Clear - medium body PVC solvent cement

Code	Description	Qty.
55922	¼ pt.	24
55924	½ pt.	24
55926	1 pt.	12
55928	1 qt.	12
55916	1 gal.	4

Fast Setting for use on PVC pipe and fittings Schedule 40 up to and including 6" and 1 ¼" Schedule 80.*

See recommended use chart on page 8



Electrical Conduit 633L Clear/Gray - medium PVC body solvent cement

Code	Description	Qty.
55980	½ pt. - clear	24
55983	1 pt. - clear	12
55985	1 qt. - clear	12
55986	1 gal. - clear	4
55979	1 gal. wide mouth - clear	4
55995	1 pt. - gray	12
55996	1 qt. - gray	12

Fast setting for use on electrical PVC conduit and fittings through 6" for Schedule 40 and Schedule 80.*

See recommended use chart on page 8



Arctic™ 616L Clear - medium body PVC solvent cement

Code	Description	Qty.
55919	1 pt.	12
55948	1 qt.	12
55953	1 gal.	4

Fast setting use on PVC pipe and fittings through 6" for Schedule 40 and 1 ¼" for Schedule 80.*
For cold weather application

See recommended use chart on page 8



Gold™ 844L Clear - heavy body PVC solvent cement

Code	Description	Qty.
55950	¼ pt.	24
55951	½ pt.	24
55952	1 pt.	12
55954	1 qt.	12
55955	1 gal.	4

Medium setting for use on PVC pipe and fittings Schedule 40 and 80 through 12"*.

See recommended use chart on page 8



*For thinner wall pipe applications, please contact RectorSeal. Max VOC per SCAQMD 1168/316A or BAAQMD Method 40: 510 g/L.