

Slotted Polypro Flush Plug

- With or without threaded brass insert
- Combine with FIP adapters to make your own cleanouts
- Plugs are durable, glass-filled polypropylene:
 - Will not seize or weld in ABS or PVC fittings
 - Acid resistant and chemically inert
 - More durable than traditional ABS or PVC plugs



878-40



Available with threaded brass insert for cleanout covers.


SUPPLY

DRAINAGE

SUPPORT

APPENDIX

White Polypro Item No	Black Polypro Item No	Plug Size	Pkg	Min Qty	Case Qty
PLUGS WITH THREADED BRASS INSERT					
878-15	879-15	1½"	B	25	25
878-20	879-20	2"	B	25	25
878-25	879-25	2½"	B	25	25
878-30	879-30	3"	B	25	25
878-35	879-35	3½"	B	25	25
878-40	879-40	4"	B	25	25
878-50	879-50	5"	B	20	20
878-60	879-60	6"	B	8	8
878-15PK	879-15PK	1½"	C*	25	25
878-20PK	879-20PK	2"	C*	25	25
878-25PK	879-25PK	2½"	C*	25	25
878-30PK	879-30PK	3"	C*	25	25
878-35PK	879-35PK	3½"	C*	25	25
878-40PK	879-40PK	4"	C*	25	25
PLUGS WITHOUT THREADED BRASS INSERT					
878-015	879-015	1½"	B	25	25
878-020	879-020	2"	B	25	25
878-025	879-025	2½"	B	25	25
878-030	879-030	3"	B	25	25
878-035	879-035	3½"	B	25	25
878-040	879-040	4"	B	25	25
878-015PK	879-015PK	1½"	C*	25	25
878-020PK	879-020PK	2"	C*	25	25
878-025PK	879-025PK	2½"	C*	25	25
878-030PK	879-030PK	3"	C*	25	25
878-035PK	879-035PK	3½"	C*	25	25
878-040PK	879-040PK	4"	C*	25	25



flush pipe plug

842-9 series fitting socket ring

Sch. 40 hub

2" - 4" plugs can be used with our 842-9 series fitting socket rings for an inexpensive threaded access hole cover.