4-VALVE ALUMINUM MANIFOLD

We know that manifolds are your lifeline. So, when we decided to retool the features and design, we were meticulous down to the last detail.



Extra Confidence

Built to last with a forged aluminum body. Designed to be leak-resistant with replaceable stainless steel valve seats, SAE-style O-rings and a securely seated, large sight glass.



Rubberized handles are optimally sized for quick and painless turns.



Front-mounted hose positions give you easier access.



Quick On The Job

Get faster vacuum pulls with a true 3/8" bore throughout the valve.



Comfortable Grip

A rubberized handle makes it easier to use in wet and dirty environments.



Glows in the Dark

Light-activated paint illuminates, so you won't be left in the dark.



Pressure Indicator Ring

A pressure reminder allows you to set the pressure ring and reference it later.



4-Valve Aluminum Manifold 1839120

4-VALVE ALUMINUM MANIFOLD

Product Specifications

Item Numbers/Product Descriptions						
Refrigerants	With 60" Hoses and Ball Valve Adapters	Without Hoses	Temp.	Pressure Range Low	Pressure Range High	
R410A	1839109 4V410H	1839111 4V410	F/C	-30" HG/300/ 500 psi	0/800 psi	
R12-22-502A	1839115 4V1222502H	1839117 4V1222502	F	-30" HG/120/ 350 psi	0/500 psi	
R12-22-134A	1839120 4V1222134H	1839121 4V1222134	F	-30" HG/120/ 350 psi	0/500 psi	
R22-134A-404A	1839122 4V22134404H	1839124 4V22134404	F	-30" HG/120/ 350 psi	0/500 psi	
R22-407C-410A (Heat Pump)	1839128 4V22407410H	1839129 4V22407410	F	0/800 psi	0/800 psi	
R22-404A-410A	1839130 4V22404410H	1839132 4V22404410	F	-30" HG/300/ 500 psi	0/800 psi	
R134A-404A-407C	1839135 4V134404407H	1839137 4V134404407	F	-30" HG/120/ 350 psi	0/500 psi	
Accuracy	Class 1 -	1% Accuracy (full sc	ale)			
Gauge Connection Type 1/8" NPT I		Male Fitting				
Valve Type	Double C	ring Piston Style				
Valve Seat (Orifice)	Replaceable Stainless Steel (SAE-style straight thread with O-ring)			O-ring)		
Sight Glass	Bonded	Bonded steel with SAE-style straight thread with O-ring				
Vacuum Port	3/8" full	3/8" full bore (quantity 1)				
Charge Ports	1/4" (qua	1/4" (quantity 3)				
Hoses Included	1839143 H60BVS4 60" Hoses with Ball Valve Adapters - Set of 4					
Dimensions						
Length Width Height	8-7/8" 4" 7-1/8" without hook	8-7/8" 4" 7-1/8" without hook				
Weight	7.1 lbs.	3.4 lbs.				