Quick Connect and Screw Connect


Thruster® Kits

The Air/Acetylene Thruster® Kit comes with adjustable flame tips and a fuel conserving Thruster® handle. Excellent for plumbing or repair work in very tight work areas. Select either "quick connect"

or "screw connect" tips and either

"B" tank or "MC" tank regulators.











	Part#	UPC#	Regulator	Tips	Handle	
	KTAQ23	89007	RB Acetylene Regulator	ATQ2, ATQ3 Thruster® Tips	TH7	
	KTAQ23MC	89008	89008 RMC Acetylene Regulator ATQ2, ATQ3 TI		Quick Connect	
Quick Connect	KTAQ3	89005	RB Acetylene Regulator	ATQ3 Thruster® Tip	Handle with	
Connect	КТАОЗМС	89006	RMC Acetylene Regulator	ATQ3 Thruster® Tip	Fuel-Conserving	
	KTAQ34	89009	RB Acetylene Regulator	ATQ3, ATQ4+ Thruster® Tips	Pilot Valve	
	KTA23	89002	RB Acetylene Regulator	AT2, AT3 Thruster® Tips	TH5 Screw Connect	
Screw	KTA23MC	89003	RMC Acetylene Regulator	AT2, AT3 Thruster® Tips		
Connect	KTA3	89000	RB Acetylene Regulator	AT3 Thruster® Tip	Handle with	
	КТАЗМС	89001	RMC Acetylene Regulator	AT3 Thruster® Tip	Fuel-Conserving	
	KTA34	89004	RB Acetylene Regulator	AT3, AT4+ Thruster® Tips	Pilot Valve	

+ATQ4 and AT4 tips must be used with a 40 cu. ft. or larger cylinder and regulator delivery pressure set at 15 PSIG. Kits include H12 [12.5 ft.] Acetylene Hose, W05 Tank Key w/chain. Regulators fitted with protective rubber gauge boots.

		Part#	UPC#	Copper Tub Solder	ing Capacity Braze			Tips		
	0.11	ATQ2	43135	1/8" to 1"	1/8" to 7/8"		A	Air/Acetylene	P /	
	Quick Connect	ATQ3	43136	5/8" to 3"	3/8" to 21/8"			injection tips that produce	F	
		ATQ4+	43137	1 ¹ / ₈ " to 4"	⁷ / ₈ " to 3"	ATQ2		a quiet flame		AT2
	Screw Connect	AT2	43130	1/8" to 1"	1/8" to 7/8"			that is completely		AIZ
		AT3	43131	⁵ / ₈ " to 3"	³ / ₈ " to 21/ ₈ "			🖥 adjustable.		
Ų		AT4+	43132	1 ¹ / ₈ " to 4"	⁷ / ₈ " to 3"	4	#	ATQ4	T4 🏢	
						#	ATQ3		AT3	U

