

# "A", "B" and "AB" Connections



# Hoses

**FOR U.S. JOBS**  
UNIWELD EMPLOYS OVER 300 WORKERS

Uniweld flexible Oxyfuel Hoses are color coded, have 8-sided crimp ferrules and are capable of withstanding high working pressures for reliability and long work life.

**HLP14B**



**H32A**

**Hose Spring**



**H12**

*Hose Spring (Part#SHLP) may be added to Acetylene or LP gas hoses by adding an (S) for one spring or (SS) for two springs (one @ each end) to the hose Part#. Example: H12S, H12SS/HLP14BS, HLP14BSS*

**4 Parts & Accessories**

	Oxyacetylene Twin Hose 3/16" I.D., Max. W.P. 200 psi			
	Part#	UPC#	Length	Connection
<b>Oxyacet. Twin Hose</b>	H32A	43510	12.5 ft.	"A"
	H32B	43512	12.5 ft.	"B"
	H32AB	43511	12.5 ft.	"AB**"
	H33A	43513	25 ft.	"A"
	H33B	43515	25 ft.	"B"
	H33AB	43514	25 ft.	"AB**"
	H34A	43516	50 ft.	"A"
	H34B	43517	50 ft.	"B"

\*\*"AB" - "A" fitted one end, "B" fitted opposite end

	LP Gas Single Hose 3/16" I.D., Max. W.P. 125 psi			
	Part#	UPC#	Length	Connection
<b>LP Gas Single Hose</b>	HLP10	43530	3 ft.	"A"
	HLP10B	43531	3 ft.	"B"
	HLP11	43533	6 ft.	"A"
	HLP11B	43534	6 ft.	"B"
	HLP13	43537	25 ft.	"A"
	HLP13B	43538	25 ft.	"B"
	HLP14	43541	12.5 ft.	"A"
	HLP14B	43542	12.5 ft.	"B"

	Acetylene Single Hose 3/16" I.D., Max. W.P. 200 psi			
	Part#	UPC#	Length	Connection
<b>Acetylene Single Hose</b>	H11	43500	6 ft.	"A"
	H11B	43501	6 ft.	"B"
	H12	43502	12.5 ft.	"A"
	H12B	43503	12.5 ft.	"B"
	H13	43504	25 ft.	"A"
	H13B	43505	25 ft.	"B"

	Oxy/LP Gas Grade "T" Twin Hose 3/16" I.D., Max. W.P. 200 psi			
	Part#	UPC#	Length	Connection
<b>Oxy/LP Grade "T" Twin Hose</b>	H32AT	43560	12.5 ft.	"A"
	H32BT	43561	12.5 ft.	"B"
	H32ABT	43562	12.5 ft.	"AB**"

\*\*"AB" - "A" fitted one end, "B" fitted opposite end



**H32AT**

Reference Information: "A" = 3/8" - 24 "B" = 9/16" - 18



Uniweld Products, Inc. Fort Lauderdale, FL 33312 U.S.A. Customer Service: 800.323.2111  
info@uniweld.com • www.uniweld.com

**35**