

555 FLEXFIX®

HVAC

UL LISTED TAPE



Backing:	Printed Biaxially-Oriented Polypropylene Film
Adhesive:	Acrylic
Liner:	N/A
Specifications:	UL 181B-FX Listed
Colors:	Metallic
Available Size:	1.89 in x 120.3 yd (48 mm x 110 m)

Applications

- Tough, contractor-grade closure system for sealing Class 1 flexible air ducts and connectors
- Seals bubble and reflective insulation materials
- Suitable for metal to metal connections in HVAC and refrigeration applications

Features

Benefits

UL 181B-FX Listed

Acrylic Adhesive

Biaxially-Oriented Polypropylene Film

Low VOC Content

- Meets code requirements for sealing flexible air ducts and connections
- Can contribute toward satisfying EA Credit 1 (Optimize Energy Performance) under LEED®
- Aggressive, high tack bond
- Low-odor adhesive
- Mold and moisture-resistant
- Tough and durable
- Hand tearable for ease of use
- 181B-FX printed for easy inspector identification
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.1 mils	79 µm	ASTM D-1000
Adhesion to Steel	45 oz/in	4.92 N/cm	PSTC-101
Tensile Strength	34 lb/in	59.54 N/cm	ASTM D-1000
Installation Temperature	-10 to 180 °F	-17 to 82 °C	
Operating Temperature	-40 to 212 °F	-40 to 100 °C	
VOC Content	< 1 g/L		
Recommended Storage Conditions: 32 - 90 °F at 50% RH ± 2%			
Standard Shelf Life (at 25 °C): 24 months from date of manufacture			

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.