




Premium Grade Duct Tape



Backing:	PE Coated Cloth				
Adhesive:	Rubber				
Liner:	N/A				
Colors:	Silver, Black, Red, White, OD, Dark Blue				
Specifications:		Tested in accordance with UL 723			
Standard Sizes:		48mm x 55m, 72mm x 55m			

Applications

- Waterproof repairs
- Heavy-duty packaging and bundling
- Seaming & securing underlayment materials
- Plastering applications

•

- Heavy-duty contractor and manufacturing uses
- Media-blast protection
- Seaming & sealing for heavy PE sheeting and tarps •

Features	Benefits		
PE-Coated Cloth Backing	 High tensile strength for difficult applications Abrasion and puncture resistant Crisp, straight tear Moisture, solvent, and chemical resistant 		
Natural rubber based adhesive	 Aggressive adhesion to all surfaces - including extremely rough materials 		
Low VOC Content	Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®		

Typical Test Values

	Standard UOM		Metric UOM		Test Method
Total Thickness	13.0	mils	0.330	mm	ASTM D-1000
Adhesion to Steel	95	oz/in	10.39	N/cm	PSTC-101
Tensile Strength	50	lb/in	87.56	N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F		4 to 93 °C		
Elongation	13%				ASTM D-1000
Smoke Developed	20				In accordance with UL723
Flame Spread	15	5			In accordance with UL723
VOC Content	<1 g	g/L			

Recommended Storage Conditions: 32-90 °F at 50% RH ± 2%

Standard Shelf Life (at 25C): 36 months from date of manufacture. the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryplastics.com 9/30/15