




## **Multi-Purpose Foil Tape**



Backing: 2.0 mil Aluminum Foil

Adhesive: Synthetic Rubber

Liner: Unbleached Natural Kraft Paper

Colors: Aluminum

Specifications: UL 723 Classified

Standard Sizes: 48mm x 46M, 72mm x 46M

## **Applications**

 Taping joints and seams in duct work for A/C, heating, and ventilation systems

- General purpose industrial and automotive uses
- Insulation seaming and patching

Features Benefits

2.0 mil Aluminum Foil Backing	<ul> <li>Conformable to fit corners and joints</li> <li>UV and moisture resistant</li> <li>Mold and mildew resistant</li> </ul>
Synthetic Rubber Adhesive	<ul> <li>Non-solvent for less odor and low VOC content</li> <li>Extreme high tack, aggressive bond to surfaces</li> <li>Good all-weather performance</li> </ul>
UL 723 Classified	<ul> <li>Meets flammability requirements for use in construction and marine applications</li> </ul>
Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®</li> </ul>

**Typical Test Values** 

	Standard UOM	Metric UOM	Test Method
Total Thickness	5.0 mils	0.127 mm	ASTM D-1000
Foil Thickness	2.0 mils	0.051 mm	ASTM D-1000
Adhesion to Steel	130 oz/in	14.22 N/cm	PSTC-101
Tensile Strength	15 lb/in	26.27 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Smoke Developed	15		
Flame Spread	10		
VOC Content	<1 g/L		

Recommended Storage Conditions: 32-90 °F at 50% RH  $\pm$  2% Standard Shelf Life (at 25C): 36 months from date of manufacture.

accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

