

ABM-HOOD & ABM-HOOD-200

ABM EasyHood

The ABM EasyHood captures air speed values from air supply or return/exhaust grilles in residential or commercial buildings, and easily converts that into an airflow volume reading. To accomplish this, the ABM EasyHood is used with an ABM-200 Airflow & Environmental Meter (or ABM-100 Airflow Meter) and a smartphone having the latest, free, CPS Link™ app installed.

KEY FEATURES:

- Test and Balance reports - automatically generated
- Easy, accurate and affordable HVAC airflow measurement in a lightweight, compact housing
- Measures airflow in grilles up to 12" x 12" (.3m x .3m) or up to 24" x 24" (.6m x .6m) with the included Expansion Hood
- Use smartphone and free CPS Link™ app to display, store and send data
- Also measures temperature, wet bulb, dew point and relative humidity (ABM-200)
- Accuracy, calibration, certification - in accordance with ANSI / AMCA standards

ADDITIONAL FEATURES WHEN USED WITH FREE CPS LINK™ APP

- Client Lists- Enter and retain client information
- Job Tracker- Create and retain record of services performed
- Geolocation- Record where (global coordinates) and when (time stamp) tests performed



**Smartphone not included*



Up to 12" x 12"
(.3 x .3 m) grilles



Up to 24" x 24"
(.6 x .6 m) grilles

Easy, Convenient Display Screens (When Using ABM-200 or ABM-100 and CPS Link App)



CPS Link™
US Patent No. 9,043,161



Download on the
App Store



GET IT ON
Google Play

Version 4.3 or higher



Connect with us on social media

CPS reserves the right to make changes to, or discontinue any product or service identified in this publication without notice. CPS advises its customers to ensure they have obtained the latest and most current version of any relevant information before placing any orders.
©CPS PRODUCTS. ALL RIGHTS RESERVED.



ABM EasyHood



SPECIFICATIONS

ABM-HOOD

Hood Opening	12" x 12" (.3 m x .3 m)
Expansion Hood Opening	24" x 24" (.6 m x .6 m)
Weight (with Expansion Hood)	4.75 lb. (2.15 kg)
Hood Size (with Expansion Hood)	17.75" H x 25" W x 25" D (.45 m x .63 m x .63 m)

ABM-HOOD-200 (When Used With ABM-200 Meter)

Wireless Connection Range	≤100 ft. (30.5 m)
Airflow Volume Regular Test	Range: 35-1,200 CFM (59-2,039 M³/H)
Airflow Low Volume Test	Range: 7-100 CFM (12-170 M³/H)
RH Range	Range: 0-85% Accuracy: ±4%
Operating Temperature	Range: 0 °F to 140 °F Accuracy: ±0.7 °F (-18 °C to 60 °C) (0.4 °C)
Auto Power Off	No connection or 30 sec after closing app
Battery Type (3.0 V)	Inside ABM-200 (CR2450 Coin Cell, Lithium)
Battery Life	> 500 hrs.
Calibration, Certification	Accuracy verified in accordance with ANSI AMCA 201-207 Airflow Rate Device Verification. Airflow calibration and certification tests performed at a 3rd party AMCA Certified Laboratory in accordance with ANSI/AMCA 210-ANSI/AMCA 51 test methods.
Warranty	1 Year (including ABM-HOOD)

PACKAGING

	ABM-HOOD & ABM-HOOD-200	ABM-HOOD	ABM-HOOD-200	ABM-HOOD or ABM-HOOD-200	ABM-HOOD	ABM-HOOD-200
	H x W x D, In (cm)	Weight, Lbs (kg)	Weight, Lbs (kg)	Product Qty Per	UPC	UPC
Color Box	14.12" x 16.62" x 16.75" (36 x 42 x 43 cm)	9.56 lbs (4.33 kg)	9.81 lbs (4.44 kg)	1	750377103094	750377103100
Corrugated Shipping Box	15.25" x 17" x 17.5" (39 x 43 x 45 cm)	11.5 lbs (5.21 kg)	11.75 lbs (5.32 kg)	1		

ABM-HOOD & ABM-HOOD-200 include:



Airflow capture hood



Expansion hood accessory



Low airflow adapter



Color box



Padded carrying case



Owner's manual

Included with ABM-HOOD-200



ABM-200 Airflow & Environmental Meter

Purchased Separately



ABM-100 Airflow Meter

LTABMH0617A