



**Catalog Number T (3/10 - 30A)  
125Vac or Less  
Edison Base  
Dual-Element, Time-Delay**

Amp Ratings T (Amp)					
3/10	1-1/8	2-1/4	4	7	15
4/10	1-1/4	2-1/2	4-1/2	8	20
1/2	1-4/10	2-8/10	5	9	25
6/10	1-6/10	3	5-6/10	10	30
8/10	1-8/10	3-2/10	6	12	—
1	2	3-1/2	6-1/4	14	—

**T Specifications**

Dual-Element, Time-Delay

**Voltage Rating:** 125Vac

**Amp Rating:** 3/10 - 30 Amps

**Interrupting Rating:** 10,000 RMS Symmetrical Amps

**Agency Approvals:**

UL Listed, Guide JEFV, File E 12112

**Benefits:**

- Heavy duty dual-element construction for motor circuits.
- Edison base threads into non-rejection fuse receptacles.
- Superior overload and short-circuit protection.

**Recommended Box Cover Units:**

Refer to page 137 in this catalog.



**Catalog Number TL (15 - 30A)  
125Vac or Less  
Edison Base  
Time-Delay**

Amp Ratings TL (Amp)			
15	20	25	30

**TL Specifications**

Time-Delay

**Voltage Rating:** 125Vac

**Amp Rating:** 15 - 30 Amps

**Interrupting Rating:** 10,000 RMS Symmetrical Amps

**Agency Approvals:**

UL Listed, Guide JEFV, File 12112

**Benefits:**

- Time-delay construction withstands light motor loads.
- Edison base threads into non-rejection fuse receptacles.
- For upgrade refer to "T" fuse.

**Recommended Box Cover Units:**

Refer to page 137 in this catalog.