


# SUBMITTAL INFORMATION

## Adapter Flange (UFA200-S-x style)




### UNI-FLANGE® SERIES 200 ADAPTER FLANGE FOR STEEL PIPE

Set Screw - AISI 4140 Steel;  
Tensile 190,000 psi  
minimum. Heat treated to  
35-39 Rockwell C and zinc  
plated for corrosion resistance


Flange - Ductile Iron per ASTM  
A536, Grade 65-45-12. Drilling  
to AWWA Class D and E,  
ANSI B16.1 (125 lb. cast iron),  
or ANSI B16.5 (150 lb. steel)

Finish: Shop coat

Color Code: Gray for steel  
applications



Gasket - SBR (Buna-S)  
gasket supplied with the  
Uni-Flange Adapter Flange



NOM. PIPE SIZE	STEEL PIPE		APPROX. WT. LBS.	PRESSURE RATING PSI	SET SCREWS		FLANGE			No. OF BOLT HOLES	BOLT CIRCLE DIA.	✓ SUBMITTED ITEM(S)
	OD (IN.)	CATALOG No.			NUMBER	SIZE	OD A	THICKNESS B	THICKNESS C			
2"	2.38	UFA200-S-2	4.2	200	2	1/2"x1"	6"	1-13/16"	3/4"	4	4-3/4"	
2-1/2"	2.88	UFA200-S-25	6.0	200	4	1/2"x1"	7"	1-13/16"	3/4"	4	5-1/2"	
3"	3.50	UFA200-S-3	6.5	200	4	1/2"x1"	7-1/2"	1-13/16"	3/4"	4	6"	
4"	4.50	UFA200-S-4	8.0	200	4	1/2"x1"	9"	1-7/8"	3/4"	8	7-1/2"	
5"	5.56	UFA200-S-5	10.5	200	8	1/2"x1"	10"	1-7/8"	3/4"	8	8-1/2"	
6"	6.63	UFA200-S-6	11.0	200	8	1/2"x1"	11"	1-7/8"	3/4"	8	9-1/2"	
8"	8.63	UFA200-S-8	19.0	200	8	5/8"x1-1/4"	13-1/2"	2-1/4"	7/8"	8	11-3/4"	
10"	10.75	UFA200-S-10	28.0	175	12	5/8"x1-1/4"	16"	2-15/16"	1"	12	14-1/4"	

### FEATURES

- Restraint is provided by a set screw locking device similar to that used in mechanical joint retainer glands
- The gasket is an SBR (Buna-S) transition gasket. Available with optional EPDM or NBR (Buna-N) gasket
- Designed for ease of on-site installation. Eliminates bolt hole alignment problems and allows for pipe deflection
- Series 200 adapter flanges are not recommended for use on PVC pipe. Use the Uni-Flange® Series 900 flanges instead
- Optional uni-torque set screws are available for use with Series 200 adapter flanges for steel pipe, Schedule 40 and up. To order, add "-UT" to the catalog number. Example: UFA200-S-6-UT
- Optional stainless steel set screws, type 410 per ASTM F593, are available for Series 200 adapter flanges. To order, add "-SS" to the catalog number. Example: UFA200-S-6-SS.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



**The Ford Meter Box Company, Inc.**

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

02/19/20

Submitted By: